

iDS-7108HQHI-M1/S















- Deep learning based human and vehicle targets classification of Motion Detection 2.0
- Deep learning-based perimeter protection
- H.265 Pro+/H.265 Pro/H.265 video compression
- HDTVI/AHD/CVI/CVBS/IP video input
- Audio via coaxial cable
- Up to 12-ch IP camera input (up to 6 MP)
- Encoding ability up to 1080P @ 15 fps





Function

Targets classification

Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning based perimeter protection

Compression and Recording

H.265 Pro+ video compression improves encoding efficiency, and reduces data storage costs Support 1080P @ 15 fps encoding

Storage and Playback

1 SATA interface (up to 10TB capacity per HDD)

Smart search for efficient playback

Network & Ethernet Access

Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management

Specification

Motion Detection 2.0			
Human/Vehicle Analysis	Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms cau by objects like leaves and lights; Quick search by object or event type is supported;		
Perimeter Protection			
Human/Vehicle Analysis	Up to 4-ch		
Recording			
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264		
	When 1080p Lite mode is not enabled:		
	4 MP lite/3 MP/1080p/720p/VGA/WD1/4CIF/CIF;		
Encoding Resolution	When 1080p Lite mode is enabled:		
	4 MP lite/1080p lite/720p lite/VGA/WD1/4CIF/CIF		






Network				
Total Bandwidth	96 Mbps			
Remote Connection	64			
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF			
Network Interface	1, RJ45 10M/100M self-adaptive Ethernet interface			
Wi-Fi	Connectable to Wi-Fi network by Wi-Fi dongle through USB interface			
Auxiliary Interface				
SATA	1 SATA interface			
Capacity	Up to 10 TB capacity for each disk			
Alarm In/Out	N/A			
USB Interface	Real panel: 2 × USB 2.0			
General				
Power Supply	12 VDC, 1.33 A			
Consumption	≤ 12 W			
Working Temperature	-10 °C to +55 °C (+14 °F to +131 °F)			
Working Humidity	10% to 90%			
Dimension (W \times D \times H)	$200 \times 200 \times 45 \text{ mm } (7.9 \times 7.9 \times 1.8 \text{ inch})$			
Weight	≤ 1 kg (2.2 lb)			

Available Model

iDS-7108HQHI-M1/S(标配)(C)(样机),iDS-7108HQHI-M1/S(中性)(C)(样机),

Physical Interface



No.	Description	No.	Description
1	Video and coaxial audio in	5	AUDIO IN, RCA connector
2	HDMI interface	6	LAN network interface and
			USB interface
3	VGA interface	7	12 VDC power input
4	AUDIO OUT, RCA connector	8	GND





Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com **Hikvision Russia** T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com